

Specifications		4KCHANGER-TC1
Power		DC 24V / 1.5A
POE		NO
Extension		NO
AV output		HDMI 19Pin Female
Dimensions (L-W-H)		7.2 in (184mm) x 3.1 in (80mm) x 3.6 in (90mm)
Product Weight		appx. 735 g
Package Box Dim. (L-W-H)		9.8 in (248 mm) x 7.7 in (195 mm) x 3.7 in (95 mm)
Package Weight		appx. 1268 g
Audio format		Dolby True HD/DTS HD/Dolby Atoms/ Dolby Digital 5.1 / Dolby Digital Plus/ DTS 5.1/LPCM
HDMI Max Frequency		297MHz
HDMI Max Bandwidth		8.91Gbps
AV Input Resolutions	Mini DP	4096 x 2160, 3840 x 2160, 2560 x 1600, 2560 x 1440, 1920 x 1200, 1920 x 1080, 1600 x 1200, 1600 x 900, 1280 x 720, 1024 x 768, 800 x 600
	Type-C	
	HDMI	
	VGA	
Charging	USB 2.0 A	Support 5V / 2.0A
	USB 3.1 C	Support 5V / 2.0A
Output HDMI Length to Display		4K/AWG 28--2m; 4K/AWG 26--5m
Ethernet Pass-Through		YES
Operation temperature		23°F ~ 104°F (-5°C ~ 40°C)
Storage temperature		5°F ~ 131°F (-15°C ~ 55°C)
Operation humidity range		5 to 85%RH (No Condensation)
Storage humidity		5 ~95%RH (No Condensation)
Max. Analog Resolutions		1920*1080 60 Hz
Max. Digital Resolutions		3840*2160 60Hz and 4096*2160 60Hz

Unit Number	Description
4KCHANGER-TC1	4KCHANGER Table Connective with input of Type C, VGA+3.5mm Audio, Mini DP & HDMI, auto-detect sources, switch botton, single HDMI output
4KCHANGER-TC2	4KCHANGER Table Connective with a Extender for distance extention and connection via 30M RJ45 Cat. 6 ; input : Type C, VGA+3.5mm Audio, Mini DP & HDMI, auto-detect sources, switch botton, single HDMI output