

# 4KVIEWER SERIES

**aegis 4KVIEWER series** is an advanced and high performance quad view system that allow users to manage up to 4 AV sources. It allows the user to connect and control up to 4 AV or 4 PCs switches via a single set of keyboard and mouse. It provides various display modes such as Picture in Picture, Picture by Picture, Picture on Picture and users free styles. It is easy to drag, drop, resize, reposition and disable images as users' wants. Same flexibility for audio functions. Users can also switching between 4 PCs and enter in a selected PC to work on. Its set up is simple; just plug cables to appropriate ports then ready to play!

## Features

- Multi-view console controls up to 4 AV HDMI / 4PCs on one screen
- Flexible Display Modes: Quad View, Picture in Picture (PiP), Picture by Picture (PbP), Picture on Picture (PoP), Full Screen and other user free style by dragging, resizing and/or repositioning.
- Superior video quality – Up to 4K (4096 x 2160 @ 30Hz)
- Push buttons, OSD, IR Remote Control or Keyboard/Mouse
- Up to 3 profiles of free style can be saved
- Flexibility of disable images and selection of audio source functions
- Image faded out and faded in function
- Compliant with HDMI 1.4
- Console keyboard mouse emulation / bypass feature that support most multimedia keyboards, mouse and multifunction mice
- No installation routines, no software configuration needed
- Drag, Drop, enlarge, reduce and save the free style display

# SPECIFICATION

Product Model		4KVIEWER-KVM-4	4KVIEWER-HDMI-4
Product Image			
General	Input Ports	Video: HDMI Jack x 4 KVM: USB-B Jack x 4 Console: USB-A Jack X 2(Keyboard / Mouse) Press Button X 4 Infrared: Infrared Receiver Module X 1 Power: Locking DC Jack X 1	Video: HDMI Jack x 4 Console: USB-A Jack X 2 (Keyboard / Mouse) Press Button X 4 Infrared: Infrared Receiver Module X 1 Power: Locking DC Jack x 1
	Output Ports	Video: HDMI Jack x 1	Video: HDMI Jack x 1
	HDMI Version	HDMI 1.4	HDMI 1.4
	HDCP Version	HDCP 1.4	HDCP 1.4
	USB Version	USB 2.0	USB 2.0
	Resolution	Up to 4KX2K/30Hz	Up to 4KX2K/30Hz
	Deep Color	Up to 12 bit	Up to 12 bit
	Audio	Up to 8 Channels (7.1)	Up to 8 Channels (7.1)
	Infrared	38KHz Frequency	38KHz Frequency
	Distance	28AWG-2M / 26AWG-5M -4K 28AWG-2M / 26AWG-5M -1080p	28AWG-2M / 26AWG-5M -4K 28AWG-2M / 26AWG-5M -1080p
	Power	100~240V, 12VDC / 2.0Amp.	100~240V, 12VDC / 2.0Amp.
	Consumption	24 Watt Max.	24 Watt Max.
Physical	Product Dimension	(L) 8.3in X (W) 5.7in X (H) 2.0in (210mm X 146mm X 52mm)	(L) 8.3in X (W) 5.7in X (H) 2.0in (210mm X 146mm X 52mm)
	Product Weight	1.84 lb / 829g	1.83 lb / 819g"
	Package Dimension	258mm X 198mm X 97mm	258mm X 198mm X 97mm
	Package Weight	1247g	1237g
	Package Content	4KVIEWER-KVM-4 X 1 PCS Infrared Controller X 1 PCS Universal Power Adapter X 1 PCS Screw X 4 PCS User Manual X 1 PCS"	4KVIEWER-HDMI-4 X 1 PCS Infrared Controller X 1 PCS Universal Power Adapter X 1 PCS Screw X 4 PCS User Manual X 1 PCS
Environmental	Operation Temperature	32°F - 104°F (0°C - 40°C)	32°F - 104°F (0°C - 40°C)
	Storage Temperature	32°F - 176°F (0°C - 80°C)	32°F - 176°F (0°C - 80°C)
	Humidity	20% - 90% (Non-Condensing)"	20% - 90% (Non-Condensing)

## 4KVIEWER-KVM-4

## 4KVIEWER-HDMI-4

