

4KCHANGER-TC2

4K MULTI INPUT CONVERTER



簡介

4KCHANGER-TC2 允許透過單條 CAT.6 纜線將一台 HDMI、雙向紅外線和雙向 RS232 連接至最多 30 公尺，適用於電腦、筆記型電腦、藍光播放器、遊戲機和其他 HDMI 來源裝置。支援 4Kx2K/60Hz UHD 解析度，具有 12 位深色和無損壓縮音訊，使 4KCHANGER-TC2 成為家庭娛樂、公司會議、商業廣告和其他應用的聰明選擇。

主要特點：

- HDMI 來源裝置包括機頂盒、藍光播放器、電腦、筆記型電腦、遊戲機、媒體播放器和攝影機。
- HDMI 接收裝置包括 LED/LCD 監視器、LED/LCD 電視、投影機和 AV 接收器。
- Mini DisplayPort 來源裝置包括電腦、筆記型電腦和平板電腦。
- VGA 來源裝置包括電腦和筆記型電腦。
- USB 3.1 Type C 來源裝置包括電腦、筆記型電腦、平板電腦和行動電話。
- HDMI 2.0 Premium 認證纜線 - 強烈推薦
- Mini DisplayPort 1.2 認證纜線 - 強烈推薦。
- USB 3.1C 認證纜線 - 強烈推薦。

硬體規格

Transmitter Specification

HDMI Bandwidth	600MHz / 18.0Gbps
HDMI Resolution	480P, 720P, 1080P/24, 30, 50, 60Hz, 4Kx2K/24, 30, 60Hz.
Mini DisplayPort Resolution	800x600, 1024x768, 10280x1024, 1600x900, 1600x1200, 1920x1080, 1920x1200, 2560x1440, 3840x2160, 4096x2160
VGA Resolution	1024x768, 1280x1024, 1600x900, 1600x1200, 1920x1080
USB 3.1 C Resolution	1024x768, 10280x1024,1600x900, 1600x1200, 1920x1080 1920x1200, 2560x1440, 3840x2160, 4096x2160
HDMI Output Resolution	480P, 720P, 1080P/24, 30, 50, 60Hz, 4Kx2K/24, 30, 60Hz. VGA video in only supports 1920x1080p as output resolution
Audio Format	PCM 2 Channel at 48KHz
HDCP	2.2
Input Port	Mini DisplayPort X 1 HDMI X 1 VGA X 1 Audio X 1 -3.5mm Stereo Jack USB 3.1 C X 1 Ethernet X 1 - RJ45 at Cat.5e/6 (Pass Thru)
Output Port	RJ45 X 1 USB 2.0 A X 1 -5V/ 1.5 Amp -BC 1.2 USB 3.1 C X 1- 5V/ 2.0 Amp Ethernet X 1 - RJ45 at Cat.5e/6 (Pass Thru)
Control Port	Select button X 1 -
Power Supply	24VDC / 1.5 Amp (US / UK / AUS / EU Power Plug)
Power Consumption	36 W - Max.
Chassis Material	Metal
Panel Color	Silver
Operating Temperature	0°C -40°C / 32°F -104°F
Storage Temperature	-15°C -55°C / 5°F -131°F
Humidity	5 - 85% RH (Non-Condensing)
Dimension LXWXH	7.2 in (184 mm) X 3.1 in (80 mm) X 3.6 in (90 mm)
Weight	1,270 g

Receiver Specification

HDMI Bandwidth	225MHz / 6.75Gbps
HDMI Output Resolution	480P, 720P, 1080P/24, 30, 50, 60Hz, 4Kx2K/50, 60Hz. VGA video in only supports 1920x1080p as output resolution
Audio Format	PCM 2 Channel at 48KHz
HDCP	2.2
Input Port	RJ45 X 1
Output Port	HDMI X 1
Power Supply	POC
Chassis Material	Metal
Chassis Color	Black
Operating Temperature	0°C -40°C / 32°F -104°F
Storage Temperature	-15°C -55°C / 5°F -131°F
Humidity	5 - 85% RH (Non-Condensing)
Dimension LXWXH	4.3 in (110 mm) X 2.17 in (55 mm) X 0.94 in (24 mm)
Weight	125 g