# 4K MULTI INPUT CONVERTER

## 4KCHANGER-TC1  Datasheet

## INTRODUCTION

4KCHANGER-TC1 is a multi-format connectivity box that provides AV , Networking and USB charging connectivity in a conference room or classroom. 4KCHANGER-TC1 with Auto-detect source function to switching proper AV signal input. You also can press select button to switching four different AV input sources. 4KCHANGER-TC1 also supports Ethernet port to connect local network system for internet service.

## FEATURES

- ✅ HDMI Source device includes SetTop Box, BD Player, Computer, Laptop, Game Console, Media Player and Camcorder.

- ✅ HDMI Sink device includes LED/LCD Monitor, LED/LCD TVs, Projector and AV Receiver.

- ✅ Mini DisplayPort Source device includes Computer, Laptop and Tablet.

- ✅ VGA Source device includes Computer and Laptop.

- ✅ USB 3.1 Type C Source device includes Computer, Laptop, Tablet and Mobile Phone.

- ✅ HDMI 2.0 Premium Certified Cable-Highly recommended

- ✅ Mini DisplayPort 1.2 Certified Cable-Highly recommended.

- ✅ USB 3.1C Certified Cable-Highly recommended.

| 4KCHANGER-TC1Specification | |
|---|---|
| Input Port | Mini DisplayPort X 1<br>HDMI X 1<br>VGA X 1<br>Audio X 1 -3.5mm Stereo Jack<br>USB 3.1 C X 1<br>Ethernet X 1 - RJ45 at Cat.5e/6<br>( Pass Thru) |
| Output Port | HDMI X 1<br>USB 2.0 A X 1 -5V/ 1.5 Amp BC 1.2<br>USB 3.1 C X 1- 5V/ 2.0 Amp<br>Ethernet X 1 - RJ45 at Cat.5e/6<br>( Pass Thru) |
| Control Port | Select button X 1 - |
| Power Supply | 24VDC / 1.5 Amp (US,UK,EU Power Plug) |
| Power Consumption | 36 W - Max. |
| Chassis Material | Metal |
| Panel Color | Silver |
| Operating Temperature | 0℃ -40℃ / 32℉ -104℉ |
| Storage Temperature | -15℃ -55℃ / 5℉ -131℉ |
| Humidity | 5 - 85% RH (Non-Condensing) |
| Dimension LXWXH | 7.2 in (184 mm) X 3.1 in (80 mm) X 3.6 in (90 mm) |
| Weight | 738 g |