



HDMI 1X2 SPLITTER

SPP-HDMI-1200

INTRODUCTION

aegis's SPP-HDMI-1200 HDMI Splitter is a product which can distribute HDMI signal without loss to one or more high definition display device such as HDTV. It can optimize your home theater system to the best effect. HDMI signal is distributed from source device such as DVD, Satellite Receiver, Set-Top Box, DV Camera, A/V Receiver and other HDMI enabled device to high definition display device such as HDTV and HDMI Flat panel Display.

FEATURES

- ✓ Fully HDMI 1.4 specification compliant..
- ✓ Support high resolutions: 480i/p, 576i/p, 720i/p, 1080i/p, 4Kx2K @25/30Hz.
- ✓ Support 30/36 dark, extended color space support, including: SYCC601、Adobe RGB、Adobe YCC601
- ✓ Blu-ray DVD 24/50/60fs/HD-DVD/xvYCC.
- ✓ Audio formats DTS-HD/Dolby-TrueHD/LPCM7.1/DTS/Dolby-AC3 and DSD.
- ✓ Extend the transmission distance and improve transmission signal.
- ✓ Compatible with DVI by using HDMI to DVI adapter.
- ✓ Support 3D

SPP-HDMI-1200 Specification

HDMI Source Input Port	1
Display Device Output Port	2
Source Port Connector	19 PIN HDMI
Display Device Port Connector	19 PIN HDMI
HDCP Compliant	YES
Single Link Range	3840*2160
Input Video Signal	0.5-1.0 Volts P-P
Input DDC Signal	5 Volts P-P(TTL)
Deep Color	48 Bit
HDMI Version	HDMI1.4b
Bandwidth	Up to 340Mhz
Signal Speed	Up to 3.4Gbps
The length of input cable	1080P≤20M, 4k2k≤15M HDMI Cable
The length of output cable	1080P≤20M, 4k2k≤15M HDMI Cable
The cable standard	26AWG HDMI1.4
Vertical Frequency Range	60Hz
Power Consumption (max.)	5Watts
Operation Temperature	-15°C to +55°C
Working Voltage	DC 5V1A
Power Adaptor	5V 1A
Net Weight	0.139Kg

