



1X4 HDMI SPLITTER

SPP-UHD-4000

INTRODUCTION

The aegis SPP-UHD-4000 1x4 HDMI 2.0 Splitter simultaneously one route HDMI source to four routes HDMI display. It supports resolution up to 4K2K@60Hz (4:4:4) and HDCP 2.2. This product supports audio extract from HDMI source to optical and analog output. It can be selected COPY, AUTO modes EDID setting. Output supports bypass and downscaler (4K->1080P) function.

FEATURES

- ✔️ HDCP2.2/HDCP1.4 compliant
- ✔️ Support 18Gbps video bandwidth
- ✔️ Supports HDMI resolution up to 4K2K@50/60Hz (4:4:4), as specified in HDMI 2.0b.
- ✔️ Support digital and analog audio extract output from HDMI source
- ✔️ Output ports support signal bypass and 4K->1080P downscaler function via the dial switch on panel
- ✔️ EDID can be selected COPY and AUTO modes via the dial switch on panel
- ✔️ Support HDMI audio format: LPCM, Dolby Digital/Plus/EX, Dolby True HD, DTS, DTS-EX, DTS-96/24, DTS High Res, DTS-HD Master Audio, DSD

SPP-UHD-4000 Specification

HDMI Compliance	HDMI 2.0b
HDCP Compliance	HDCP 2.2 and HDCP 1.4
Video Bandwidth	18Gbps
Video Resolution	720P50/60Hz 1080P50/60Hz, 4K2K24Hz 4K2K30Hz, 4K2K@50/60Hz (4:4:4)
HDMI Audio Formats	LPCM, Dolby Digital/Plus/EX, Dolby True HD, DTS, DTS-EX, DTS-96/24, DTS High Res, DTS-HD Master Audio, DSD
Color Space	RGB, YCbCr 4:4:4, YCbCr 4:2:2
Output Port	4×HDMI Type A [19-pin female] 1×L/R Audio out [3.5mm Stereo Mini-jack] 1×Optical out [S/PDIF]
Input ports	1×HDMI Type A [19-pin female]
Power Supply	Input: AC100~240V 50/60Hz Output: DC5V/1A (US/EU standards · CE/FCC/UL certified)
Power Consumption	3.5W - Max.
Chassis Material	Metal
Chassis Color	Black
Operating Temperature	0°C ~ 40°C / 32°F ~ 104°F
Storage Temperature	-20°C ~ 60°C / -4°F ~ 140°F
Humidity	20~90% RH (non-condensing)
Dimension	180mm(W)×62mm(D)×14mm(H)
Weight	227g

